

Data sheet Humadent®-Unit Ozone-Therapy-Generator (for dentists)

- LED-Display
- Digital-display for vacuum- and ozone concentration
- Ozone valve (dust-tight / air-tight barrier)
- Sterilizable Ozone valve
- Ozone concentration to regulate from 0 up to 70 µg/ml
- Automatic cleancheck
- Vacuum- / suck function
- Integrated catalyzer
- Justified photometric
- Footswitch for remote control
- Handpiece with 3 different winded dental Luer cannula
- 24 month warranty

Technische Daten:

- | | |
|---------------------------|---|
| ➤ Power supply: | 230 V AC 50/60 Hz |
| ➤ Power consumption: | 50 VA |
| ➤ Ozone generator: | Ozone concentration: 0 up to 70 µg/ml +/-5% |
| ➤ Gas flow: | 300 ml/min. |
| ➤ Catalyzer: | Service life min. 5 yeras |
| ➤ Cleaning: | commercially available washing-up liquid, DO NOT USE solvents (acetone) |
| ➤ Desinfection: | Sagrotan / Kodan or similar |
| ➤ Service life: | 24 month |
| ➤ Dimensions (LxBxH): | 28 x 30 x 12 cm |
| ➤ Weight: | 3,80 kg |
| ➤ Referred position: | CE 0535, EUROCAT / BSI Institute for Certification and Testing |
| ➤ Product classification: | EU directive 93/42 EEC for medical equipment, Appendix II b |

